

0G1CP1E


ELECTRIC PASTA COOKER, SINGLE WELL, 26 lts



ANGELO PO

RANGE FEATURES

- Top: 18-10 stainless steel (12/10 mm gauge)
Free-standing structure with top, front panels, sides and control consoles in 18-10 stainless steel; back panels in stainless steel.
Top, sides, back, front panels and control consoles with satin scotchbrite finish.
Side-by-side top configurations with secure fixing between units.
IPX5 protection rating on all units.
CE approval of all gas products.



FUNCTIONAL FEATURES

- Cooking well continuously welded to the top, with recess to trap starch and foam in the well; pressed well with large rounded edges and high-flow vertical drain line for rapid emptying; AISI 316L 15/10 mm stainless steel well with polished finish for improved cleaning; cooking well designed for use with 1/1 G.N. containers.
- Front overspill and starch removal area with drain outlet and perforated stainless steel basket drainage shelf in front of well.
- Water filler and top-up taps with command on control panel and spout located on overspill and starch removal area.
- Drain line in 18-10 stainless steel controlled by ball valve with easy access lever.
- Adjustable heating controlled by 5 position knobs, max 9 kw, with command on control panel.
- Capacity well 26 litres. Well useful dimensions: cm. 26x34x28h.
- Safety unit prevents pan operating without water.
- Specific output: 529 W/litre.
- Heat-resistant knobs with screen printed markings and reference index printed on control console.
- Hinged door.
- Height adjustable floor-mounted feet in 18-10 stainless steel - floor clearance 180 mm, with non-scratch sole in insulating plastic material.
- The pasta cooker can be equipped with: single well lid in AISI304 18-10 stainless steel, set of two baskets (useful dimensions cm 11x30,6x20 h) in flat micro-streched mesh in AISI 316L stainless steel, single basket, useful dimensions cm.11x30,6x20h, single basket, useful dimensions cm.23x30,6x20h, single basket, useful dimensions cm.8,5x8,5x20h.



TECHNICAL FEATURES

- Direct heating controlled by stainless steel heating element in the well.
- Easy access to all parts from front cabinet and control panel.

Width	Cm	35
Depth	Cm	70
Height	Cm	90

Electric Power kW 9

Standard connection V-Hz 400V 3~ / 50Hz ÷ 60Hz